

CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the October/November 2015 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2015 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

bestexamhelp.com

® IGCSE is the registered trademark of Cambridge International Examinations.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

- 1 (a) (gravitational) force proportional to product of masses
and inversely proportional to square of separation
either point masses *or* particles *or* 'size' \ll separation
- M1
A1 [2]
- (b) gravitational force provides the centripetal force
- B1
- either* $GMm/x^2 = mx\omega^2$ *or* mv^2/x
either $\omega = 2\pi/T$ *or* $v = 2\pi x/T$ and working to $GM = 4\pi^2 x^3/T^2$
- M1
A1 [3]
- (c) *either* use of gradient of graph *or* line through origin so can use single point
or line shown extrapolated to origin
- B1
- gradient = $(4.5 \times 10^{14})/0.35$
 $6.67 \times 10^{-11} \times M = 4\pi^2 \times (4.5 \times 10^{14} \times 10^9)/(0.35 \times \{24 \times 3600\}^2)$
- correct conversion for km^3 and power of 10
correct conversion for day^2
 $M = 1.02 \times 10^{26}$ kg
- C1
C1
A1 [4]
- 2 (a) total volume of molecules negligible compared to that of containing vessel
no intermolecular forces
molecules in random motion
time of collision small compared with the time between collisions
large number of molecules
any two
- B2 [2]
- (b) in a real gas there is a range of velocities *or* must take the average of v^2
- B1 [1]
- (c) (i) *either* $p = \frac{1}{3} \rho \langle c^2 \rangle$
or $1.0 \times 10^5 = \frac{1}{3} \times 1.2 \times \langle c^2 \rangle$
- C1
- $\langle c^2 \rangle = 2.5 \times 10^5$
 $c_{\text{r.m.s.}} = 500 \text{ m s}^{-1}$
- C1
A1 [3]
- (ii) $T \propto \langle c^2 \rangle$
 $\langle c^2 \rangle = 2.5 \times 10^5 \times 480/300$
 $= 4.0 \times 10^5 \text{ m}^2 \text{ s}^{-2}$ (*allow ECF from (c)(i)*)
- C1
A1 [2]
- 3 (a) same temperature
no (net) transfer of thermal energy (between the bodies)
- B1
B1 [2]
- (b) (i) 41.3 K
- B1 [1]
- (ii) 330.4 K
- B1 [1]

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

$$\begin{aligned} \text{(c)} \quad \Delta E_k &= \frac{3}{2} \times 1.9 \times 60 \\ &= 171 \text{ J} \end{aligned}$$

C1

$$\begin{aligned} \text{work done} &= p\Delta V \\ &= 1.2 \times 10^5 \times 950 \times 10^{-6} \\ &= 114 \text{ J} \end{aligned}$$

C1

C1

$$\begin{aligned} \text{thermal energy} &= 114 + 171 \\ &= 285 \text{ (290) J} \end{aligned}$$

A1 [4]

4 (a) acceleration/force proportional to distance from a fixed point or displacement

M1

either acceleration/force and displacement in opposite directions
or acceleration/force (always) directed towards a fixed point/mean position/equilibrium position

A1 [2]

$$\text{(b)} \quad h\rho g = Mg/A$$

B1

$$h \times 790 \times 4.9 \times 10^{-4} = 70 \times 10^{-3} \text{ leading to } h = 0.18 \text{ m or } 18 \text{ cm}$$

A1 [2]

$$\begin{aligned} \text{(c) (i) 1.} \quad \omega^2 &= (790 \times 4.9 \times 10^{-4} \times 9.81) / (70 \times 10^{-3}) \\ &= 54.25 \end{aligned}$$

C1

$$\omega = 7.37 \text{ (rad s}^{-1}\text{)}$$

$$\text{period (= } 2\pi / \omega) = 0.85 \text{ s}$$

C1

$$t_1 = 0.43 \text{ s}$$

A1 [3]

$$\text{2. } t_3 = 1.28 \text{ s (allow 2 s.f.)}$$

A1 [1]

$$\text{(ii) energy of peak} = \frac{1}{2}M\omega^2x_0^2$$

B1

$$\begin{aligned} \text{change} &= \frac{1}{2} \times 70 \times 10^{-3} \times 54.25 \{ (2.2 \times 10^{-2})^2 - (1.0 \times 10^{-2})^2 \} \\ &= 7.3 \times 10^{-4} \text{ J} \end{aligned}$$

C1

A1 [3]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

- 5 (a) charges in metal do not move
no (resultant) force on charges so no (electric) field
(allow 1/2 for “no field inside sphere”) B1 [2]
B1
- (b) *either* average field strength = $\frac{1}{2} (28 + 54) \text{ NC}^{-1}$ C1
average force = $8.5 \times 10^{-9} \times \frac{1}{2} (28 + 54)$ C1
= $3.49 \times 10^{-7} \text{ N}$
change in potential energy = $3.49 \times 10^{-7} \times 2.0 \times 10^{-2}$
= $7.0 \times 10^{-9} \text{ J}$ (allow 1 s.f.) A1
(allow range 54 ± 1)
or (for a point charge) $V = Ex$ (C1)
 $\Delta V = (54 \times 5.0 \times 10^{-2}) - (28 \times 7.0 \times 10^{-2})$ (C1)
change in potential energy = $8.5 \times 10^{-9} \times (2.70 - 1.96)$
= $6.3 \times 10^{-9} \text{ J}$ (allow 1 s.f.) (A1)
(allow range 54 ± 1)
or ΔV is area under curve (C1)
 $\Delta V = 0.74 \text{ V}$ (C1)
change in potential energy = $8.5 \times 10^{-9} \times 0.74$
= $6.3 \times 10^{-9} \text{ J}$ (allow 1 s.f.) (A1) [3]
(allow range 0.70 to 0.84)
- 6 (a) magnetic fields are equal in magnitude/strength/flux density M1
magnetic fields are opposite in direction M1
fields superpose/add/cancel to give zero/negligible resultant field A1 [3]
- (b) core causes increase in magnetic flux in the solenoid/induced poles in core B1
or field induced in core M1
changing flux threads/cuts the turns on the solenoid A1
(by Faraday’s law) an e.m.f. is induced in the solenoid A1
by Lenz’s law, this e.m.f. opposes the battery e.m.f. [4]
- 7 (a) (i) $V_0 (= 14\sqrt{2}) = 19.8 (20) \text{ V}$ A1 [1]
(ii) $\omega (= 2\pi \times 750) = 4700 \text{ rad s}^{-1}$ A1 [1]
- (b) large amount of charge required to charge capacitor M1
capacitor would charge and discharge rapidly/in a very short time M1
or capacitor would charge and discharge 750/1500 times per second
 $I = Q/t$, so large current A1 [3]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

- 8 (a) $hc/\lambda = \Phi + E_{\text{MAX}}$
 $h = \text{Planck constant, } c = \text{speed of light/e.m. radiation}$ M1
A1 [2]
- (b) (i) gradient of line is hc
 h and c are both constants M1
A1 [2]
- (ii) $\Phi = 2.28 \times 1.6 \times 10^{-19}$
 $= 3.65 \times 10^{-19} \text{ (J)}$ C1
- $hc/\lambda_0 = 3.65 \times 10^{-19}$
- $\lambda_0 = (6.63 \times 10^{-34} \times 3.0 \times 10^8)/(3.65 \times 10^{-19})$ C1
 $= 5.45 \times 10^{-7} \text{ m}$ A1 [3]
- 9 (a) energy required to separate the nucleons (in a nucleus)
or energy required to separate the protons and neutrons in a nucleus M1
(or energy released when nucleons combine (to form a nucleus)/energy released
when protons and neutrons combine to form a nucleus)
- either completely or to infinity A1 [2]
(either free protons and neutrons or from infinity)
- (b) (i) either different forms of same element or nuclei having same number of
protons with different numbers of neutrons M1
A1 [2]
- (ii) 1784 MeV (accept min. 3 s.f.) A1
7.57 MeV A1 [2]
- (c) (i) $\lambda = \ln 2 / (7.1 \times 10^8 \times 365 \times 24 \times 3600) = 3.1 \times 10^{-17} \text{ s}^{-1}$ B1 [1]
- (ii) $A = \lambda N$
 $5000 = 3.1 \times 10^{-17} \times N$ C1
 $N = 1.61 \times 10^{20}$
- mass = $235 \times (1.61 \times 10^{20}) / (6.02 \times 10^{23})$ C1
= 0.063 g (accept min. 2 s.f.) A1 [3]

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

Section B

- 10 (a)** correct LED symbol B1
separately connected between V_{OUT} and earth with opposite polarities M1
diode B 'pointing' from V_{OUT} to earth A1 [3]
(ignore protective resistors)
- (b)** diode in V_{OUT} line M1
diode 'pointing' towards V_{OUT} from earth A1
relay coil connected between V_{OUT} and earth M1
switch connected across lamp A1 [4]
*(if a diode is placed across the relay it must point down otherwise max. 2/4;
one diode but wrong direction max. 3/4)*
- 11 (a)** e.g. scattering (in metal)
non-parallel beam (not just "A closer than B")
reflection (from metal)
diffraction in the metal/lattice
any two B2 [2]
- (b) (i)** 1. ratio = $e^{\mu x}$
= $\exp(0.27 \times 4.0)$ C1
= 2.94 (2.9) A1 [2]
2. ratio = $\exp(0.27 \times 2.5) \times \exp(3.0 \times 1.5)$ C1
= 1.96×90
= 177 (180) A1 [2]
- (do not penalise unit error more than once)*
- (ii)** each ratio gives measure of transmission B1
ratios (in **(i)**) very different so good contrast B1 [2]
- 12 (a) (i)** serial-to-parallel converter B1 [1]
(ii) digital-to-analogue converter *or* DAC B1 [1]
(iii) (audio) amplifier *or* AF amplifier B1 [1]
- (b) (i)** 4 A1 [1]
(ii) 1011 A1 [1]
- (c)** correct levels at 0.25 ms intervals
0, 8, 11, 10, 15 A1
and 7, 4 A1
series of steps, each of depth 0.25 ms M1
voltage levels shown in correct intervals A1 [4]

Page 7	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	43

- 13 (a) advantage: e.g. shorter time delay
greater coverage over a long time B1
- disadvantage: e.g. satellite needs to be tracked
more satellites for (continuous) coverage/communication
(any sensible suggestions) B1 [2]
- (b) (i) frequencies linking Earth with satellite B1
- 6 GHz is uplink frequency }
4 GHz is downlink frequency } (allow vice versa) B1 [2]
- (ii) either signal from Earth to satellite is attenuated greatly
or downlink must be amplified greatly before transmission B1
- downlink would swamp uplink unless frequencies are different B1 [2]