MARK SCHEME for the May/June 2012 question paper

for the guidance of teachers

9702 PHYSICS

9702/52

Paper 5 (Planning, Analysis and Evaluation), maximum raw mark 30

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2012 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Mark Scheme: Teachers' version	Syllabus	Paper			
	GCE AS/A LEVEL – May/June 2012	9702	52			
1 Planning (15	1 Planning (15 marks)					
Defining the pro	blem (3 marks)					
P1 v is the indep	endent variable and $ heta$ is the dependent variable or variable $ heta$	ry <i>v</i> and measure	e <i>θ.</i> [1]			
	P2 Keep the (shape <u>and</u>) size/volume/surface area/mass of balloon/helium <u>constant</u> Do not credit 'same balloon'.					
P3 Keep the terr	perature (air/helium/balloon) <u>constant.</u>		[1]			
 Methods of data collection (5 marks) M1 <u>Labelled</u> diagram of apparatus: <u>balloon</u>, string fixed and <u>method of producing wind</u>. Method of producing wind to be approximately horizontal to balloon. 						
M2 Suspend ma	ss from balloon.		[1]			
M3 Method to ch distance from	ange wind speed, e.g. change setting, variable power n fan.	supply/resistor/c	hange [1]			
M4 Method to me	easure wind speed, e.g. wind speed indicator/detector,	, anemometer	[1]			
	easure angle – use protractor or rule for measurement shown correctly on diagram or explained in text.	s for trigonometry	y methods. [1]			
Method of analy A1 Plot a graph	sis (2 marks) of tan θ against $1/v^2$.		[1]			
A2 Relationship	valid if straight line through origin		[1]			
	ations (1 mark) ving blades of the fan (safety screen, switch off when void air stream into eye.	changing experin	nent); [1]			
 Large wind s Additional de 	(4 marks) points might include peed to produce measurable deflection/large cross-sec tail on measuring angle e.g. use a large protractor, pro		[4] Illoon.			
4 Measuring ai5 Adjust height6 Reason for a7 Keep window	r speed at point where balloon is positioned. of fan so that air flow is horizontally aligned to the ball dding mass to increase stability/deflection. /s shut/air conditioning switched off/use of wind tunnel palloon to become stable.		<u>s</u> .			
	io computer methodo					

Do not allow vague computer methods.

[Total: 15]

Page 3	Page 3 Mark Scheme: Teachers' version		Paper
	GCE AS/A LEVEL – May/June 2012	9702	52

2 Analysis, conclusions and evaluation (15 marks)

Part	Mark	Expected Answer	Additional Guidance	
(a)	A1	Gradient = $\frac{1}{2}\sqrt{\frac{T}{\mu}}$	Allow equivalent, e.g. $\sqrt{\frac{T}{4\mu}}$	
(b)	T1	1/L / m ⁻¹ or (1/L) / m ⁻¹	Allow 1/L (m ⁻¹), 1/L / 1/m, 1/L (1/m)	
	T2	1.83 or 1.835 2.08 or 2.083 2.35 or 2.353 2.50 or 2.500 2.82 or 2.817 3.13 or 3.125	Values must correspond to table. A mixture of 3 s.f. and 4 s.f. is allowed	
	U1	From \pm 0.01 or \pm 0.02, to \pm 0.05	Allow more than one significant figure.	
(c) (i)	G1	Six points plotted correctly	Must be within half a small square. Penalise 'blobs' (more than half a small square). Ecf allowed from table.	
	U2	All Error bars in 1/ <i>L</i> /m ⁻¹ plotted correctly.	Check second and last point for accuracy. Must be accurate within half a small square.	
(ii)	G2	Line of best fit	If points are plotted correctly then lower end of line should pass between (1.8, 250) and (1.8, 254) and upper end of line should pass between (3.18, 450) and (3.2, 448). Allow ecf from points plotted incorrectly – examiner judgement.	
	G3	Worst acceptable straight line. Steepest or shallowest possible line that passes through <u>all</u> the error bars.	Line should be clearly labelled or dashed. Should pass from left of top error bar to right of bottom error bar or right of top error bar to left of bottom error bar. Mark scored only if all error bars are plotted.	
(iii)	C1	Gradient of best fit line	The triangle used should be at least half the length of the drawn line. Check the read offs. Work to half a small square. Do not penalise POT. (Should be about 140)	
	U3	Uncertainty in gradient	Method of determining absolute uncertainty Difference in worst gradient and gradient.	
(d) (i)	C2	Value of μ using gradient	μ = 7.5/gradient ² Gradient must be used. (Should be about 0.00037 or 3.7 × 10 ⁻⁴)	
	C3	kg m ^{-1} or N Hz ^{-2} m ^{-2}	Allow other correct units e.g. N s ² m ⁻² or Pa s ² or N (Hz m) ⁻²	
(ii)	U4	10% + 2 × percentage uncertainty in gradient	Check working. Must be larger than 10%.	

Page 4		Mark Scheme: Teachers' version GCE AS/A LEVEL – May/June 2012		Syllabus 9702	Paper 52
(e)	C4	<i>r</i> given to 2 or 3 s.f. and in the range 1.15 × 10^{-4} to 1.18 × 10^{-4}		Allow 1.2 to 2 s.f. Penalise 1 s.f. or >3 s.f.	
	U5	(d)(ii) / 2	Check working	if not (d)(ii) / 2	

[Total: 15]

Uncertainties in Question 2

- (c) (iii) Gradient [U3] Uncertainty = gradient of line of best fit – gradient of worst acceptable line Uncertainty = ½ (steepest worst line gradient – shallowest worst line gradient)
- (d) (ii) [U4]

Percentage uncertainty = $10 + 2 \frac{\Delta m}{m}$

Percentage uncertainty =
$$\frac{\frac{\max T}{4 \times \min m^2} - \mu}{\mu} \times 100$$

Percentage uncertainty =
$$\frac{\frac{\min T}{4 \times \max m^2} - \mu}{\mu} \times 100$$

(e) (ii) [U5]

Percentage uncertainty =
$$\frac{\max r - r}{r} \times 100$$

Percentage uncertainty = $\frac{\min r - r}{r} \times 100$