## MARK SCHEME for the October/November 2012 series

## 9702 PHYSICS

9702/31

Paper 3 (Advanced Practical Skills 1), maximum raw mark 40

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2012 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.



	Page 2			Mark Scheme	Syllabus	Paper
				GCE AS/A LEVEL – October/November 2012	9702	31
1	(b)	(ii) Values of raw <i>L</i> in range 2.0 cm $\leq L \leq$ 8.0 cm consistent with unit.			[1]	
		(iii)	Valu	e of $\theta$ < 90° with unit. No raw value greater than 0.5° p	recision.	[1]
	(c)	Five sets of readings of <i>L</i> , <i>m</i> and $\theta$ scores 5 marks, four sets scores 4 marks etc. Incorrect trend then –1. Major help from Supervisor –2. Minor help from Supervisor –1.				c. [5]
		Rar	nge: n	$m_{\rm min} \le 0.100  { m kg},  m_{\rm max} \ge 0.350  { m kg}.$		[1]
				neadings: umn heading must contain a quantity and a unit where a must conform to accepted scientific convention e.g. <i>m</i> /k		[1] , <i>θ  </i> °.
Consistency: All values of <i>L</i> must be given to the nearest mm.		•		[1]		
		Significant figures: All values of <i>m</i> sin $\theta$ must have the same number of significant figures as, or one mor than, the least number of significant figures in <i>m</i> and $\theta$ .				[1] ne more
	Calculation: Values of <i>m</i> sin $\theta$ calculated correctly.			[1]		
	(d)	Ser Sca botl Sca		Axes: Sensible scales must be used. Awkward scales (e.g. 3:10) are not allowed. Scales must be chosen so that the plotted points occupy at least half the graph grid both <i>x</i> and <i>y</i> directions. Scales must be labelled with the quantity that is being plotted. Scale markings must be no more than three large squares apart.		
			All o Dian Che	ing of points: bservations in the table must be plotted on the graph gri neter of plots must be $\leq$ half a small square (no blobs). ck that the points are plotted correctly. Work to an accur the <i>x</i> and <i>y</i> directions.		[1] mall square in
			Judg	lity: oints in the table must be plotted (at least 4) for this mar ge by the scatter of all the points about a straight line. oints must be within ± 0.01 kg in the <i>m</i> sin $\theta$ direction of		
		(ii)	Judg Ther Allov	of best fit: ge by balance of all the points on the grid (at least 4) abo re must be an even distribution of points either side of th v <u>one</u> anomalous point only if clearly indicated (i.e. circle lidate. Line must not be kinked or thicker than half a sma	e line along the	e full length.

	Page 3			Mark Scheme	Syllabus	Paper
				GCE AS/A LEVEL – October/November 2012	9702	31
	<ul> <li>(iii) Gradient:</li> <li>The sign of the gradient must match the graph. The hypotenuse of the triangle must be at least half the length of the drawn line.</li> <li>Both read-offs must be accurate to half a small square in both the <i>x</i> and <i>y</i> direction the method of calculation must be correct.</li> </ul>					
				ercept:		[1]
		Either: Check correct read-off from a point on the line and substitution into $y = mx + c$ Read-off must be accurate to half a small square in both the x and y directions Or: Check the read-off of the intercept directly from the graph.				
	(e)	(e) Value of P = candidate's gradient. Value of Q = candidate's intercept. Do not allow a value presented as a fraction.		[1]		
		Unit for $P$ (m kg <sup>-1</sup> or cm kg <sup>-1</sup> or mm kg <sup>-1</sup> or m g <sup>-1</sup> or cm g <sup>-1</sup> or mm g <sup>-1</sup> ) and $Q$ (m or cn correct and consistent with value.				r cm or mm) [1]
						[Total: 20]
2	(a)	(ii)	Valu	e of circumference in range 30.0 – 50.0 cm to the neare	st mm with unit	. [1]
		(iii)	lf rep	blute uncertainty in circumference is between 2 mm – 6 r beated readings have been taken, then the absolute unc e. Correct method used to calculate the percentage unc	certainty can be	[1] half the
		(iv)	Valu	e of circumference within 2 cm of first value.		[1]
	(b)	(ii)		time values to at least 0.1s or 0.01s, value of $0.5 s < T$ ence of repeats.	< 2.0 s.	[1] [1]
	(c)	(i)		ond value of <i>T</i> . ond value of <i>T</i> > first value of <i>T</i> .		[1] [1]
		(ii)	Third	d value of <i>T</i> .		[1]
	(d)	(ii)		ect calculation of two values of <i>k</i> . ect calculation of third value of <i>k</i> .		[1] [1]
		(iii)		ification of significant figures in <i>k</i> linked to significant figures in <i>k</i> linked to significant figureadings")	ures in time <u>anc</u>	<u>l</u> <i>m</i> (not just [1]
		(iv)		sible comment relating to the calculated values of <i>k</i> , test rified by the candidate.	ing against a c	riterion [1]

Page 4	Page 4   Mark Scheme   Syllab		Paper
	GCE AS/A LEVEL – October/November 2012	9702	31

(e)

	(i) Limitations 4 max.	(ii) Improvements 4 max.	Do not credit
A	three results not enough /not enough results	take more readings <u>and plot a</u> graph	two results not enough /repeat readings /few readings
В	string too wide for markings on rule	use thinner string	
С	rules have different thicknesses so effective length of loop changes/ /different lengths so not a fair test	use rulers of similar thicknesses/ readings/method to take thickness into account /use rulers of the same length	
D	times are small /large uncertainty in time	use longer strings/improved method of timing	
E	difficult to judge start/ end of/complete oscillation	Position/motion sensor facing the rule /video with timer	position sensor at end or in middle
F	swings of 30 cm ruler highly damped		
G	difficult to make two loops of the same circumference	method by which this can be achieved	
Н	large uncertainty in mass	method of measuring mass more precisely	accurate balance

[Total: 20]